

# BOOST LINE



INDUSTRIAL AND CLEANING EQUIPMEN'



## Concept:

Dulevo Boost Combi has been designed to combine handiness, affordability, reliability together with a superior sweeping and scrubbing quality. High-quality components and latest technology ensure that Dulevo Boost Combi meets operational demands of our customers. The combination of two cleaning concepts has been designed in order to clean heavy industrial environment as constructions, logistics and distribution centers and many others where highest efficiency and productivity are always required.

Dulevo Boost Combi guarantees eco-friendly and efficient results, maximum productivity and low maintenance costs, in any working application.



### **Operating system:**


Dulevo Boost Combi is combining the idea of sweeping and scrubbing at the same time. First of all the sweeping unit will pick up the debris and then the scrubbing unit will clean the floor.

The design of the front located sweeping unity is based on the well known Dulevo sweeping and filtration technology to insure an effective sweeping result with full dust control. The heavy duty scrubbing deck, with three brush plates and constant floor pressure, ensures highest cleaning results even on heavily soiled surfaces.



#### **Environment:**

Environmental awareness has always been a key concern in our company. The different drive technology, battery powered and different endothermic engines combined with low water consumption and dust free sweeping are the milestones of Dulevo Boost Combi.



#### **Access and Service:**

The modular construction allows an easy access to all important sections of the machine for service and maintenance.



## **Operation and Comfort:**

Simple and reliable controls have been designed to make the machine intuitive and easy to operate. Ergonomic and comfort of Dulevo Boost Combi grant a pleasant workspace.

TECHNICAL DATA		BOOST COMBI
Sweeping path	mm	1450
Waste hopper capacity	L	210
Maximum dump hopper	mm	1350
Filtration PM10	%	99
Scrubbing path	mm	1150
Squeegee path	mm	1350
Solution tank capacity	L	220
Recovery tank capacity	L	210
Traction		Rear
Cleaning performance (EH)	m²/h	8400 (EH 7200)
Maximum speed (EH)	Km/h	7 (EH 6)
Engine	EH	Electric
	DK	Diesel Kubota
	ВК	Petrol Kubota
	GK	Lpg Kubota
Weight ( EH without battery)	Kg	1100 (EH 960)
Length	mm	2100
Width	mm	1200
Height (with roll-bar)	mm	1420 (2130)















# **DULEVO INTERNATIONAL S.P.A.**

Via G.Guareschi,1 - 43012 - Fontanellato (Parma) Italia ph: +39 0521 827711 - Fax: +39 0521 827795 info@dulevo.com - www.dulevo.com

























Ed. 00-2015 - C (copyright) 2014 Dulevo International S.p.a.

Specifications are not binding for our company and subject to change at any time without notice